


LR6-72HV 330~350M

**High Efficiency Mono Technology
(1500V Compatible)**
with advanced 5BB design to improve
power output

10-year Warranty for Materials and Processing;
25-year Warranty for Extra Linear Power Output



+3.60%

-0.55%

25-year Power
Warranty Annual
Power Attenuation
-0.55%

Complete System and Product Certifications

IEC 61215, IEC61730, UL1703
ISO 9001:2008: ISO Quality Management System
ISO 14001: 2004: ISO Environment Management System
TS62941: Guideline for module design qualification and type approval
OHSAS 18001: 2007 Occupational Health and Safety



* Specifications subject to technical changes and tests. LONGi Solar reserves the right of interpretation.

Positive power tolerance (0 ~ +5W) guaranteed

High module conversion efficiency (up to 18.1%)

Better energy yield with excellent low irradiance performance and temperature coefficient

Solid PID resistance ensured by solar cell process optimization and careful module BOM selection

Adaptable to harsh environment: passed rigorous salt mist and ammonia tests

Robust frame (40mm) withstands mechanical loading of 5400Pa for snow load on front and 2400Pa for wind load on rear side


LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203
Tel: + 86-21-61047332 Fax: +86 21- 61047377 E-mail: module@longi-silicon.com
Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.

LR6-72HV 330~350M

Design (mm)



Mechanical Parameters

Cell Orientation: 72 (6x12)

Junction Box: IP67, three diodes

Output Cable: 4mm², 1200mm in length

Connector: MC4 or MC4 compatible

Weight: 22.2kg

Dimension: 1956x991x40mm

Packaging: 26pcs per pallet

Operating Parameters

Operational Temperature: -40 °C ~ +85 °C

Power Output Tolerance: 0 ~ +5 W

Maximum System Voltage: DC1500V (IEC)

Maximum Series Fuse Rating: 15A

Nominal Operating Cell Temperature: 45±2 °C

Application Class: Class A

Electrical Characteristics

Model Number	LR6-72HV-330M		LR6-72HV-335M		LR6-72HV-340M		LR6-72HV-345M		LR6-72HV-350M	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax/W)	330	238.6	335	242.2	340	245.8	345	249.4	350	253.0
Open Circuit Voltage (Voc/V)	46.1	42.4	46.3	42.6	46.5	42.8	46.7	43	46.9	43.1
Short Circuit Current (Isc/A)	9.30	7.50	9.40	7.58	9.49	7.65	9.58	7.72	9.68	7.80
Voltage at Maximum Power (Vmp/V)	37.6	34.0	37.7	34.1	37.9	34.2	38.1	34.5	38.2	34.6
Current at Maximum Power (Imp/A)	8.78	7.02	8.89	7.11	8.97	7.18	9.05	7.24	9.16	7.32
Module Efficiency(%)	17.0		17.3		17.5		17.8		18.1	
STC (Standard Testing Conditions): Irradiance 1000W/m², Cell Temperature 25 °C, Spectra at AM1.5										
NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient Temperature 20 °C, Spectra at AM1.5, Wind at 1m/S										

Temperature Ratings (STC)


Temperature Coefficient of Isc	+0.059%/°C
Temperature Coefficient of Voc	-0.330%/°C
Temperature Coefficient of Pmax	-0.410%/°C

Mechanical Loading


Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

I-V Curve


Current-Voltage Curve (LR6-72HV-340M)



Power-Voltage Curve (LR6-72HV-340M)



Current-Voltage Curve (LR6-72HV-340M)



LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203
 Tel: + 86-21-61047332 Fax: +86 21- 61047377 E-mail: module@longi-silicon.com
 Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice. Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.