



The GXV3601 is a next generation IP camera of power and innovation. It features cutting edge H.264 real-time video compression (D1 resolution) with excellent image clarity at low-to-modest bandwidth, industry leading SIP/VoIP for full duplex 2-way audio and video streaming to mobile phones and video phones, integrated PoE, embedded analytics, large pre-/post-event recording buffer, and advanced security protection. Its unique incorporation of the most comprehensive peripheral support for alarm control, local storage expansion, and wireless network connection, creates sophisticated and best-in-class control flexibility and scalability. The GXV3601 can be managed with GSurf, Grandstream's advanced and intuitive video management software that controls up to 36 cameras simultaneously. The GXV3601 is a powerful network camera for professional surveillance environments.

Feature Highlights

- High quality Sony CCD sensor and lens to ensure razor sharp picture quality
- Advanced multi-streaming-rate real-time H.264, Motion JPEG at D1 resolution
- Alarm input & output, audio input & output, RS485, iris control
- 24MB pre-/post-event recording buffer
- USB 2.0 port and SD slot for storage/wireless network card
- Integrated Power-over-Ethernet (802.3af), optional antenna for wireless network
- Embedded video analytics, SIP/VoIP support for full duplex two-way audio as well as video streaming to mobile phones and video phones
- Built-in high performance streaming server to allow up to 16 simultaneous D1 viewers or 25 CIF viewers

Grandstream Networks, Inc. www.grandstream.com

Corporate Headquarters
1297 Beacon Street, 2nd Fl.
Brookline, MA 02446 USA
Voice: (617) 566-9300
Fax: (617) 249-1987

California Office
1301 John Reed Court
City of Industry, CA 91745
Voice: (626) 638-9172
Fax: (617) 249-1987

Dallas Office
2301 W. Plano Pkwy Suite 208
Plano, TX 75075
Voice: 469-241-0100
Fax: (617) 249-1987

Shenzhen, China
Bldg #1, No 2 Ke Fa Road
Nan Shan High Tech Industrial Park (Central)
Shenzhen, China 518057
Voice: +86 755-2601-4600
Fax: +86 755-2601-5996

Models	GXV3601-N/GXV3601W-N (NTSC)	GXV3601-P/GXV3601W-P (PAL)
Video Compression	H.264, JPEG, Motion JPEG	
Image Sensor	1/3" SONY Super HAD CCD	
Lens Type	1/3" Varifocal 3.5-8mm, DC-iris, CS mount, changeable	
Minimum Illumination (Lux)	0.015 at F1.4	
Max Video Resolution	Full D1: 720 x 576 (PAL), 720 x 480 (NTSC)	
Max Frame Rate in Max Resolution	30fps/25fps at D1 resolution (NTSC/PAL)	
Video Bit Rate	32 Kbps - 2 Mbps	
Video Output	BNC x 1, Voltage 1.0Vp-p, Resistance 75 Ω	
Audio Input	3.5mm LINE-IN	
Audio Output	3.5mm LINE-OUT	
Alarm Input	Yes - 1, Normal Open	
Alarm Output	Yes - 1, 125VAC/0.5A, 30VAC/2A	
Audio Compression	G.711, G.726	
Serial Ports	RS485	
IRIS Control	Yes	
Embedded Analytics	Motion detection (up to 16 target areas), video loss (pending)	
Pre-/post-alarm Buffer	24MB	
Snapshots	Trigger upon events, send via email/FTP	
Multi-streaming-rate for Preview & Recording	Yes	
Security	Video watermark, HTTPS, Password	
Network Port	10M/100M auto-sensing, RJ45	
Network Protocol	TCP/UDP/IP, RTP/RTCP, RTSP, DHCP, PPPoE, DDNS, HTTP, HTTPS	
Power over Ethernet (PoE)	Standard, IEEE 802.3af Class 3	
Peripheral Ports	SD 2.0, USB 2.0	
Wi-Fi (802.11b/g)	5dB external antenna (GXV3601W only)	
SIP/VoIP Support	Yes	
Dimensions (L x W x H)	155mm x 68mm x 64mm	
Weight	0.9kg	
Temperature / Humidity	-10°C- +55°C (14°F-131°F) Humidity 10-90% RH (non-condensing)	
Power	Output: 12VDC/1A; Input:100-240VAC, 50-60Hz	
Compliance	FCC Part 15, Subpart B Class B; EN 55022 Class B, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 60950-1; C-tick AS/NZS CISPR 22, CISPR 24	

