



EP CUBE

Residential Energy Storage System **NEW**

EP CUBE PRODUCT INTRODUCTION



FEATURES



Integrated hybrid inverter
Supports DC and AC input
Suitable for new and installed PV systems



Modular battery system, Easy to install and transport
Capacity options from 9.9kWh to 19.9kWh per EP Cube unit,
and up to 119.9kWh for full system



Lithium iron phosphate batteries
UL 9540A unit level thermal runaway test certification



Multiple energy storage modes
Guarantees household power supply
Seamlessly switch to backup in case of power failure



Supports Wi-Fi and cellular communication
Remotely monitor generation and consumption
Receive backup reminders prior to bad weather



Compatible with generators for long-term power outages
Can be connected to 2@50A EV chargers
Supports high current, power input and output

EP CUBE HYBRID INVERTER + BATTERIES



3-Battery Modules



4-Battery Modules



5-Battery Modules



6-Battery Modules

EP Cube system				
Hybrid inverter			1	
Battery modules	3	4	5	6
Base			1	
Hybrid inverter				
MPPTs			4	
Input current			I_{mp} 16A / I_{sc} 20A per MPPT	
PV maximum input voltage			600V _{DC}	
PV DC input voltage range			80V _{DC} - 550V _{DC}	
MPPT operating voltage			90V _{DC} - 550V _{DC}	
Allowable DC-AC ratio			2	
Nominal grid voltage			240V _{AC}	
Frequency			60Hz	
Maximum AC output, on-grid			7.6 kW	
Battery roundtrip CEC efficiency			93.93%	
Imbalance for split-phase loads			100%, maximum 3.8kW for each phase	
Energy storage				
Total energy	9.9 kWh	13.3 kWh	16.6 kWh	19.9 kWh
AC output, PV + battery				
	7.6 kW	7.6 kW	7.6 kW	7.6 kW
Full Sun, off-grid	31.6A	31.6A	31.6A	31.6A
	22 kVA (10s)	22 kVA (10s)	22 kVA (10s)	22 kVA (10s)
AC output, battery only				
	5 kW	6.5 kW	7.6 kW	7.6 kW
No Sun, off-grid	20.8A	27.0A	31.6A	31.6A
	5.4kVA (10s)	7.2kVA (10s)	9kVA (10s)	10kVA (10s)
Safety & compliance				
Protections	Integrated arc fault circuit interrupter (AFCI), PV RSD *			
	UL 1699B, UL 1741-SB, IEEE 1547, IEEE 2030.5			
Certifications	UL 1642, UL 1973, UL 9540, UL 9540A, UN 38.3			
	FCC Part 15 (Class B)			
	IEEE 693-2005 (high)			
Listing	CEC, HECO **			
General parameters				
Enclosure	NEMA 4X			
Noise	< 50dB @ 1m, front side			
Dimensions	23.62" x 47.64" x 8.66" 600 x 1210 x 220 mm	23.62" x 56.10" x 8.66" 600 x 1425 x 220 mm	23.62" x 64.57" x 8.66" 600 x 1640 x 220 mm	23.62" x 73.03" x 8.66" 600 x 1855 x 220 mm
System weight	286.6 lbs / 130 kg	352.7 lbs / 160 kg	418.9 lbs / 190 kg	485 lbs / 220 kg
Battery module weight			70lbs / 32kg	
Inverter weight			77lbs / 35kg	
Base weight			5.5lbs / 2.5kg	
Mounting options	Floor or wall mount			
Max. elevation	9,843 ft / 3,000 m			
Ambient operating temperature	14°F to 122°F / -10°C to 50°C			
Optimum operating temperature	32°F to 86°F / 0°C to 30°C			
Limited warranty				
System warranty	> 80% capacity, up to 10 years or 6,000 cycles ***			

Notes: * PVRSD support Tigo and APSmart transmitter. ** HECO in process *** Battery capacity warranty up to 10 years or 6,000 cycles (whichever occurs first).

EP CUBE SYSTEM/TECHNICAL DATA



Smart Gateway

Grid and load

Nominal grid voltage	120 / 240V _{AC}
Frequency	60 Hz
Overcurrent protection	200A
Short circuit current protection	10 kA

Microgrid interconnection

Rated current	200A
Switchover time (on-grid / off-grid)	Seamless

EP Cube interface *

Output voltage	120 / 240V _{AC}
Overcurrent protection	40A

Enhanced interface **

Output voltage	120 / 240V _{AC}
Overcurrent protection	100A
Generator control request	Yes
Generator start type	2-wire start (I/O)
EV Charger communication (optional)	RS-485

Communication

Internet connection	Wifi, Cellular (LTE, 4G)
User interface	EP Cube APP (Android & IOS)

Safety & compliance

Certifications	UL1741-SB, ICES-003 (Class B) FCC Part 15 (Class B), FCC ID IEEE 693-2005 (high)
----------------	--

General parameters

Enclosure	NEMA 4X
Noise	< 50dB
Dimensions	23.62" x 23.62" x 7.09" 600 x 600 x 180 mm
Weight	44.1 lbs 20 kg
Mounting options	Wall mount
Max. elevation	9,843 ft / 3,000 m
Ambient operating temperature	-40 °F to 122 °F / -40 °C to 50 °C

Limited warranty

System warranty	10 years
-----------------	----------

Notes: * The Smart Gateway EP Cube interface includes one EP Cube hybrid connection.
** The Smart Gateway includes two enhanced interface hardware.

CONTACT

Add: 1350 Treat Blvd. Suite 500, Walnut Creek, CA 94598, USA

Tel: +1 800 761 2990 E-mail: service.epcube@csisolar.com www.csisolar.com/na