PosiTest[®]CH Cross Hatch Adhesion Tester

Determines a coating's ability to resist separation from a substrate when a lattice pattern is cut into the coating in accordance with ISO 2409 and ASTM D3359

Features...

- Includes all tools and accessories required for cross hatch testing in accordance with ISO 2409 and ASTM D3359
- Ergonomic tool handle with non-slip grip provides comfortable all-day use
- Pivoting cutting head ensures proper positioning and equal pressure across the cutting surface
- Easy to replace, high-grade hardened steel blade with 4 cutting edges for longer testing
- Ideal for coatings up to 250 μm (10 mils) depending on blade and Standard
- Wide range of 4-in-1 cutting blades available for different Standards, coating thicknesses, and substrates. Tool is compatible with all DeFelsko cutting blades.
- Illuminated Magnifier available with 3x or 10x magnification depending on Standard
- Brush included to remove any detached flakes from the coating
- Choice of adhesive tape conforms to ISO 2409 or ASTM D3359
- Durable hard shell case keeps contents secure

Kit Options...

PosiTest *CH Cross Hatch Adhesion Test* is offered in 5 kits—3 in accordance with ISO 2409 and 2 in accordance with ASTM D3359

Use the tables below to select the appropriate blade based on the Standard and the thickness of the coating to be tested.

ISO 2409						
Coating Thickness		Specified Blade	PosiTest CH Cross Hatch Adhesion	4-in-1 Replacement		
μm	mils	(Spacing/# of Cuts)	Tester Kit	Blades		
0 - 60	0 - 2.3	1 mm / 6 Teeth*	CHKITIS06X1	CHBLADE6X1		
61 - 120	2.4 - 4.7	2 mm / 6 Teeth	CHKITIS06X2	CHBLADE6X2		
121 - 250	4.7 - 9.8	3 mm / 6 Teeth	CHKITIS06X3	CHBLADE6X3		

 * For soft substrates (e.g. wood and plaster), use 2 mm / 6 Teeth for coating thicknesses between 0 - 120 μm (0 - 4.7 mils)

ASTM D3359						
Coating Thickness		Specified Blade	PosiTest CH Cross Hatch Adhesion	4-in-1 Replacement		
μm	mils	(Spacing/# of Cuts)	Tester Kit	Blades		
0 - 50	0 - 2	1 mm / 11 Teeth	CHKITASTM11X1	CHBLADE11X1		
51 - 125	2 - 5	2 mm / 6 Teeth	CHKITASTM6X2	CHBLADE6X2		





Consumables

Replacement ISO Tape (CHDTISOTAPE) (1) Roll of ISO 2409 Tape—25 mm wide

Replacement ASTM Tape (CHASTMTAPE) (1) Roll of ASTM D3359 Tape—25 mm wide

Conforms to ISO 2409/16276-2, ASTM D3359, AS 3894.9/1580.408.4, JIS K 5600-5-6



DeFelsko Corporation • 800 Proctor Ave., Ogdensburg, New York 13669-2205 USA Toll Free 1-800-448-3835 • Tel: +1-315-393-4450 • Fax: +1-315-393-8471 www.defelsko.com • E-mail: techsale@defelsko.com



PosiTest CH ASTM Kit

© 2023 DeFelsko Corporation USA. All Rights Reserved. Technical Data subject to change without notice. Printed in USA. DTv.LW-W2307