

# Quick Start Guide

**1** If possible, place the subwoofer(s) on the same wall as the front speakers.



SVS wants you to be thrilled with the performance of your new subwoofer! Please contact our Sound Experts for personalized recommendations on room placement.

**2**

**A) Using an RCA cable, connect the A/V receiver LFE subwoofer output to the subwoofer right low Level Line in (LFE).**

**B) Connect the power cord to the subwoofer amp and the AC outlet. Set the main power switch to the ON (-) position.**

**3**

Adjust the gain to half (12 o'clock).

Confirm the Phase control is set to 0.

Confirm the Low Pass is set to Disable.

Confirm the Auto/On switch is set to Auto

**4**

**A) Run the auto-set-up function on your A/V receiver.**  
**B) Access the A/V receiver speaker set-up menu, and confirm the appropriate speaker/subwoofer crossover settings for each speaker channel.**  
**C) For additional guidance on crossover settings, visit our Merlin matching tool at [www.svsound.com/product/merlin](http://www.svsound.com/product/merlin).**

**Optional 2-Channel Stereo Set-Up**

**A) Connect the L/R outputs of the pre-amp to the L/R Line In of the subwoofer.**  
**B) Connect the L/R Line Out of the subwoofer to the L/R inputs of the loudspeaker amplifier.**  
**C) Obtain the recommended Low Pass Filter frequency setting from our Merlin matching tool.**  
**D) Adjust the Low Pass Filter to the recommended frequency setting.**  
**E) Adjust the Gain to level match your loudspeakers.**

For alternate connection options or other assistance, please contact our Sound Experts.