

Date Prepared : 04/09/2018 SDS No : Wax Buster II

#### 1. PRODUCT AND COMPANY IDENTIFICATION

GENERAL USE: 208-375-7200 PRODUCT DESCRIPTION: Ski & Snowboard base cleaner PRODUCT CODE: Wax Buster II CHEMICAL FAMILY: Solvent blend

#### MANUFACTURER

Technichem Corp 1 N Maple Grove Road Boise, ID 83704 **Emergency Contact:** Brian Rencher **Emergency Phone:** 208-375-7200 **Customer Service:** 208-375-7200 **Transportation:** 1-800-633-8253 PERS

# 24 HR. EMERGENCY TELEPHONE NUMBERS

PERS 1-800-633-8253 contract # 8575

#### 2. HAZARDS IDENTIFICATION

# **GHS CLASSIFICATIONS**

Causes skin and eye irritation. GHS LABEL



SIGNAL WORD: WARNING

# HAZARD STATEMENTS

H316: Causes mild skin irritation. H315 + H320: Causes skin and eye irritation. H227: Combustible liquid. H302 + H332: Harmful if swallowed or if inhaled.

#### **EMERGENCY OVERVIEW**

PHYSICAL APPEARANCE: Water white liquid

IMMEDIATE CONCERNS: Combustible.

# POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

SKIN: Causes skin irritation. Allergic reactions are possible.

**SKIN ABSORPTION:** A single, prolonged exposure is not likely to result in the material being absorbed through skin in harmful amount.

INGESTION: Do Not Induce vomiting, Drink pleanty of water, Consult a physician.

**INHALATION:** High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

#### REPRODUCTIVE TOXICITY

TERATOGENIC EFFECTS: None Expected.

CARCINOGENICITY: None Expected.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Chemical Name** 

Wt.% CAS



Date Prepared : 04/09/2018 SDS No : Wax Buster II

	Aliphatic Petrolleum Distillates	< 90	64742-48-9
I	D-limonene	< 15	5989-27-5

# 4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

**INGESTION:** Get immediate medical attention. Do not induce vomiting unless instructed to do so by poison center or physician.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

# SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Irritation and redness

SKIN: Irritation and redness, acid burning, which may not accure until at some point after exposure.

SKIN ABSORPTION: light headed - dizziness

**INHALATION:** light headed - dizziness

# 5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Combustible liquid.

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: None known.

**OTHER CONSIDERATIONS:** During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

HAZARDOUS DECOMPOSITION PRODUCTS: None Expected.

# 6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Mop up with detergent & water & rinse with water, or wipe up with toweling and let dry.

LARGE SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

# ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LAND SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

AIR SPILL: None known.

GENERAL PROCEDURES: Clean up spills immediately, observing precautions in Protective Equipment section.

**RELEASE NOTES:** Do not flush to sewer.

**SPECIAL PROTECTIVE EQUIPMENT:** This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

# 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Avoid contact with eyes, skin, and clothing.

HANDLING: Keep away from heat and flame.

STORAGE: Keep container closed.

STORAGE TEMPERATURE: Store in a cool place below (120) F (49) C.

ELECTROSTATIC ACCUMULATION HAZARD: None Expected.



Date Prepared : 04/09/2018 SDS No : Wax Buster II

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles) and a face shield.

SKIN: Nitrile gloves

**RESPIRATORY:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**PROTECTIVE CLOTHING:** normal work clothes

WORK HYGIENIC PRACTICES: Do not smoke when using this product or any chemicals.

**COMMENTS:** NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)
Aliphatic Petrolleum Distillates	140

PHYSICAL STATE: Liquid ODOR: Slight citrus scent ODOR THRESHOLD: None known. APPEARANCE: Water white liquid pH: NA = Not Applicable PERCENT VOLATILE: 100% FLASH POINT AND METHOD: 125 F

- FLAMMABLE LIMITS: .95 to 6.0
- AUTOIGNITION TEMPERATURE: 500 F
- VAPOR PRESSURE: .849
- BOILING POINT: 340 F
- **FREEZING POINT:** NA = Not Applicable
- MELTING POINT: NA = Not Applicable
- **POUR POINT:** NA = Not Applicable
- THERMAL DECOMPOSITION: Not Available

SOLUBILITY IN WATER: None

**EVAPORATION RATE:** water = 1 JG Base = .3

- **DENSITY:**.769
- SPECIFIC GRAVITY: .769
- VISCOSITY: Not Available

(**VOC):** < 6.4 gallon

Notes: 100% - 6.4 lbs / gallon

WEIGHT PER VOLUME: 6.4 Gallon

# **10. STABILITY AND REACTIVITY**

**REACTIVITY:** Stable. **HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.



**STABILITY:** Stable.

**CONDITIONS TO AVOID:** Oxidizing materials.

POSSIBILITY OF HAZARDOUS REACTIONS: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

INCOMPATIBLE MATERIALS: Some plastics and paints - test 1st

#### **11. TOXICOLOGICAL INFORMATION**

#### ACUTE TOXICITY

Chemical Name	ORAL LD <sub>50</sub>	DERMAL LD <sub>50</sub>
Aliphatic Petrolleum Distillates	5000	3160

SKIN CORROSION/IRRITATION: Harmful in contact with skin

SERIOUS EYE DAMAGE/IRRITATION: May cause eye irritation.

**RESPIRATORY OR SKIN SENSITISATION:** May cause allergy or asthma sysmptoms or breathing difficulties if inhaled **GERM CELL MUTAGENICITY:** None known.

# CARCINOGENICITY

**OSHA:** None Expected.

NOTES: None known.

**REPRODUCTIVE TOXICITY:** None known.

#### **12. ECOLOGICAL INFORMATION**

ENVIRONMENTAL DATA: Not Available

ECOTOXICOLOGICAL INFORMATION: Not Available

#### **13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** Do not dispose of on land, in surface waters, or in strom drains. Waste should be recycled or disposed in in accordance with regulations.

FOR LARGE SPILLS: Large amounts should be collected for re-use or consigned to a licensed hazardous waste hauler for disposal.

**PRODUCT DISPOSAL:** Disposal should be in accordance with regulations **EMPTY CONTAINER:** recycle container

# 14. TRANSPORT INFORMATION

# DOT (DEPARTMENT OF TRANSPORTATION) PROPER SHIPPING NAME: Liquid Cleaning Compound TECHNICAL NAME: Liquid Cleaning Compound

PRIMARY HAZARD CLASS/DIVISION: NA = Not Applicable

U.S. SURFACE FREIGHT CLASS: 55

# ROAD AND RAIL (ADR/RID)

PACKING GROUP: ||

LABEL: None

AIR (ICAO/IATA)

SHIPPING NAME: Flammable Liquid NOS - for air shipment only

TECHNICAL NAME: Petroleum Distillates NOS,3 PG III

UN/NA NUMBER: UN1268

PACKING GROUP: III



Date Prepared : 04/09/2018 SDS No : Wax Buster II

#### **15. REGULATORY INFORMATION**

#### **UNITED STATES**

# SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: Yes PRESSURE GENERATING: No REACTIVITY: No ACUTE: No CHRONIC: No

#### 313 REPORTABLE INGREDIENTS: None

# TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Aliphatic Petrolleum Distillates	64742-48-9
D-limonene	5989-27-5

#### **16. OTHER INFORMATION**

APPROVED BY: Brian RencherTITLE: PresidentPREPARED BY: Brian RencherDate Prepared: 04/09/2018INFORMATION CONTACT: 208-375-7200





**MANUFACTURER DISCLAIMER:** This SDS is written with the best of our chemical knowledge and with comment sense and in every day terms. If you do not understand a term or phrase please ask a supervisor.