

KX-UTG300

- HD Voice and Full Duplex Speaker Phone
- 5.0-inch Color Graphical Touchscreen
- Built-in Bluetooth®
- Two Gigabit Ethernets, PoE
- Support Panasonic KX-UTA336B Expansion Modules (up to two)
- Zero Touch Provisioning
- Two-year Warranty

Network Optimization and Touchscreen Capability

The Panasonic KX-UTG300 SIP Phone is a feature-rich and cost-effective communication solution. Providing reliable, award-winning Unified Communications hardware and business phones for more than 25 years, Panasonic has designed an enterprise-grade SIP phone that features HD voice, built-in Bluetooth® and a 5.0-inch Color Graphical Touchscreen for improved productivity and enhanced collaboration. The Panasonic KX-UTG300 SIP phone is the ideal solution for businesses of all sizes that require a reliable business communication tool and interoperability for business-class features that deliver functionality and affordability.



1.877.207.0031
panasonic.com/SIP



KX-UTG300 Specifications

KX-UTG300 SPECIFICATIONS	
LCD Display	5-inch WGA 800/480 Color Graphical TFT LCD with capacitive single touchscreen
LCD Size	5-inch 800/480 pix
LCD Backlight	Level 1 – 14
Expansion Module	KX-UTA336B (optional)
INSTALL OPTIONS	
Desk Mount Tilt	Yes—2 Positions
Wall Mount	KX-A433-B
Power Adapter	DSA-42D-482480063 (Optional for phone; must when attach KEM)
NETWORKING	
Ethernet Ports	2 Gigabit Ethernet
Power Over Ethernet (PoE)	Yes—Class 2
Bluetooth®	1 (Bluetooth wireless technology 2.0)
AUDIO FEATURES	
Audio Codec	G.711 [A-law and μ-law], G.729AB, G.722, G.726
Handset, Speaker, Headset Volume	8 levels (includes echo cancellation and distortion prevention)
Ringtones	9
Ringer Volume	Total 9 levels (0 level is off)
Headset Port	RJ9/USB
Electronic Hook Switch Control Port	RJ11 Jabra and Plantronics compatible
Hearing Aid	Compatible with Hearing Aid TIA-1083 / FCC P68.316 / FCC P68.317 / CS-03
KEYS	
Keys (total)	29
Programmable Keys	24 keys (3 pages of 8)
Navigator Key	Yes
SOFTWARE FEATURES	
Phone Book Entries	1,000
Call Log Entries	6 lines (Each line: 100 Placed Call +100 Received Call +100 Missed Call)
Conferencing	3 parties (within terminal—multi-party dependent on server)
Music on Hold	Support
IP FEATURES	
SIP Accounts	6
SIP Compatibility	RFC 3261 Standard SIP Server, BroadSoft®, Metaswitch®, Digium®
IP Version	IPv4/Pv6
DHCP Client	Yes
DNS	Yes
HTTP	Yes
HTTPS	Yes
SNTP Client	Yes
VLAN (802.1q)	Yes
QoS (DiffServ)	Yes
sRTP/TLS	Yes
RTCP	Yes
TFTP/FTP	Yes
LLDP	Yes
CDP Compatible	Yes
NAT/STUN	Yes
Refer	Yes
Single Common Firmware/Auto Firmware	Yes
XML Provisioning	Yes
WEB Setting/Service Mode	Yes
LDAP	Yes
802.1x	Yes

KX-UTG300 SPECIFICATIONS, CONT.	
CONFIGURATION	
Plug & Play Configuration	Server-based configuration, BroadSoft® Device Management Server and Metaswitch Network SIP Provisioning Server
Manual Configuration	Internal Web Configurator, Local (LCD based) Network Configuration
USB	1 port
AC Adapter	Handset 3.6W, Handsfree 6.3W
Talking	Support up to 30.24W
Operating Environment	32°F to 104°F (0°C to 40°C)
DIMENSIONS AND WEIGHT	
Lower Position	10.51" x 7.36" x 6.10" (W x D x H) (handset on cradle, stand attached)
High Position	10.51" x 6.69" x 7.08" (W x D x H) (handset on cradle, stand attached)
Weight	2.80 lb. (with handset, handset cord and stand)
CALL FEATURES	
Shared Call/Line Appearance	Yes
Flexible Line Appearance	Yes
Call Transfer	Yes
Do Not Disturb	Yes
Call Forward (conditional/unconditional)	Yes
Conferencing (local/network)	Yes
Multi-cast Paging	Yes
Call Waiting	Yes
Call Park/Call Pickup	Yes
Speed Dial/Redial	Yes
Busy Lamp Field (BLF)	Yes